
frame and more securely support the fluming-length thereon. This block will allow for the fluming being laid and supported upon foundation or bed blocks of concrete or the like laid on the ground, thereby dispensing with a trestle-frame if so desired. The fluming-length, in addition, is formed with transversely extending brace-members extending across between its top edges and moulded integrally therewith.

CONCRETE POST—A patent, No. 41243, has been taken out by Leader Vincent Orbell, of Waitaki, New Zealand. It consists of a post made in a mould, which may be opened on hinges or taken apart, the said post providing for the



securing of both plain and barb wires, and also for anchors or foot-pieces. The post may have strips for stapling or suchlike uses east in same, together with any other necessary boles.

Useful Recipes.

Cheap Varnish for Leather.

Mix well together equal quantity of gum water and white of egg. If the articles are to be handled, mix together a little water and white of egg; add less water than egg. Apply it with a camel's hair brush.

Gold Varnish for Leather.

Mix half a gallon of turpentine, 8 ounces gum sandrae, 8 ounces seed lac, 8 drams dragon's blood, 4 ounces turpentine, 8 ounces ground glass, and small quantity gamboge and turmeric. Put them in a bottle, then shake well, let it settle, pour off, and use the clear.

Red Wash for Bricks.

Dissolve 8 ounces best glue in 2 gallons hot water, and while it is hot add half a pound alum. Venetian red. Spanish brown, or yellow other to produce the colour.

Tarnished Brasses,

Brasses will not soon tarnish if they are wiped over with a little salt dissolved in vinegar after cleaning.

Fireproof Whitewash.

Mix 10 parts whitewash, 2 parts silicate of soda or potash, and a small solution of alum. Stir together before rising. The alum will prevent the wash from rubbing off.

Stucco Whitewash.

Take half a bushel clean unslaked lime, slack it with boiling water, cover it during the process. Strain the liquor through a fine sieve or strainer, add 1 peck of clean salt dissolved in hot water, 3 lbs. ground rice, to thin paste, and well stored in boiling hot, 8 onnecs best powdered Spanish whiting and 1 lb. best glue, dissolved in hot water.

Add 6 gallons of hot water to the whole mixture, stir well and let it stand a few days, covered from dirt. It should be put on quite hot. For this purpose it can be kept in a suitable kettle on a portable furnace. Half a pint will cover one square yard.

MALTHOID Roofing

COSTS LESS and LASTS LONGER!

Tis best for all purposes! It lasts longer than iron, and is far cheaper to buy. Malthoid is not affected by either heat or cold. Tis proof against the ravages of weather, and will out-last the building it covers.

See that you get the genuine Malthoid! Accept no substitute that only looks like Malthoid, but is unlike Malthoid in quality.

Get full particulars from

Aubrey Gualter & Co.

Featherston Street Wellington

McCarthy's Family Hotel

Taupo Quay,
WANGANUI

C. J. McCARTHY, PROPRIETOR

Steel Constructional Work for Architects, Contractors, Etc.

Full stocks. Quick deliveries.

A. & T. BURT, LTD.

Auckland, Wellington, Christchurch, Timaru, Dunedin, Invercargill.

London Office: Eldon St. House, E.C.